



Dimensions in mm and approximate

Cordless Table Lamp | Uno

Finish Options



Black / Matte Glass Globe
UN.TLB.BL



Brushed Brass / Specular Glass Globe
UN.TLB.BBR

(Others available on request)

Shade

Glass Globe

Lamp Base

Integral LED

Light Source

2W (1800K-2700K)

IP Rating

IP 54

Flex

N/A

Switching & Plug

Integrated Dimmer
Switch

Base Weight

1.6 kg approx.

Dimming Type

Integrated (Dim to Warm)

Certification





BATTERY TECHNICAL DATA SHEET

Cordless Table Lamp | Uno

Type	Lithium-ion Rechargeable Battery
Nominal Voltage	3.7V/5200mAh
Rated Capacity	≥5100mAh @0.2C Discharging
Charge Voltage	4.2V
Charge Current	Standard charge: 0.2C Max charge: 0.5C
Discharge Current	Standard Discharge: 0.2C Max Continue Discharge: 0.5C
Operating Temperature	Charging: 10°C ~ 45°C Discharging: -10°C ~ 45°C
Operating Life (at full output)	9 hours
Battery Charging Time	6-8 hours
Cycle Life	>80% of original capacity after 300 Cycles
Storage Temperature	-20°C ~ + 45°C
Storage humidity	≤85%
Battery Weight	95 g Approx
OV Charge	>1.2V